



#### **Product technical sheet**

## **JUNGLE 3231**







4 - 14 years

s 86 kids

89,3 m<sup>2</sup>



#### **Material specification**

- $\bullet\,$  Powder galvanized and powder coated or stainless steel construction of 80 x 80 mm profile,
- Platforms and climbing walls made of durable anti-slip and waterproof HPL plate,
- Roofs and side panels made of durable HDPE plate, resistant to weather conditions,
- Transparent polycarbonate panels with a weather-resistant print,
- Slides made of stainless steel with durable HDPE side panels,
- Stainless steel tube slide,
- Drawing board made of durable HPL plate, resistant to weather conditions,
- Maze windows made of polycarbonate, balls made of synthetic material,
- Music panels made of durable HDPE and HPL plate, resistant to weather conditions,
- Durable climbing stones made of polyester resin composite with mineral fillers,
- Steel ropes in polypropylene braid, connected with durable plastic elements, stainless steel or aluminum,
- Attested, safe seats,
- Calibrated stainless steel chains, preventing fingers entrapment,
- Stainless steel bars, ladders and handrails,
- Stainless steel screws and/or screws covered with plastic caps,
- Safe end caps on top of the structure made of rubber or polypropylene,



#### Facilitating disability



shelters



#### Intellectual development



manipulation



music



#### **Physical development**



balance

thinking



hiding



sliding



rest



passage



climbing

M: +48 793 404 991













## **Product technical sheet**


## **JUNGLE 3231**











#### **Product data**

Length	1155 cm
Width	815 cm
Total height	660 cm
Age group	4 - 14 years
Number of users	86 kids
Safety zone	89,3 m2
Free fall height	270 cm
The height of the platforms	90, 120, 150, 180, 210, 240, 270, 300, 360 cm
tube slide platform height	360 cm
slide platform height	90, 210 cm
In accordance with norm EN	1176-1:2017+A1:2023
Weight of the heaviest part	210 kg
Dimensions of the largest part	8x8x585 cm
Availability of spare parts	YES
Installation time	20 h
Color options	60

Data is subject to change without prior notice.

#### **Additional information**

- equipment adapted for the disabled; intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jamming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70 cm deep;
- slide should not be installed southwards;
- render is for reference only, the actual appearance of the equipment and its color may vary;

#### **Guarantee**



30 year guarantee -Durability of steel and 15 stainless steel structural elements



15 year guarantee - Durability of steel and stainless steel structures of mobile devices; durability of Robinia wood structural elements



10 year guarantee - Structural strength of HDPE, 100% recycled HDPE and HPL elements; structural elements made of 100% recycled material (composite)



5 year guarantee - Corrosion resistance of stainless steel and hot-dip galvanized and powder-coated steel elements, resistance to bark beetles and rotting of wooden structural elements

Detailed information in the guarantee card

Vinci Group Sp. z o.o. Seminaryjna 9 Street 99-400 Łowicz

VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991



biuro@vinci-play.com info@vinci-play.com www.vinci-play.com



### **Surfaces according to EN 1176-1:2017+A1:2023**

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
bark (A,C)  Particle size from 20 to 80	Particle size from 20	30	≤200
	to 80	40	≤300
woodchips (A,C)  Particle size from 5 to 30	30	≤200	
	to 30	40	≤300
sand or gravel (A,C)	Particle size from	30	≤200
	0,25 to 8	40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		270

#### **Product technical sheet**

## **JUNGLE 3231**

# Amount of safe surface corresponding with free fall height:

HIC 100	19,4 m²
HIC 120	2,0 m <sup>2</sup>
HIC 150	1,6 m <sup>2</sup>
HIC 180	13,4 m²
HIC 210	6,7 m <sup>2</sup>
HIC 240	23,4 m <sup>2</sup>
HIC 270	22,8 m <sup>2</sup>

Data is subject to change without prior notice.

