

Instructions Manual

For

Brazier

The **BRAZIER** is moulded out of 4mm regular iron-sheet. Along the brazier runs a handle formed as a huge iron-ring. The 4 fixed legs have a height of 20cm each and are wrought with ornaments.

Used as outdoor fireplace intended for firewood as well as charcoal/briquettes. It is also possible to place a round grid on top of the brazier, which makes the brazier suitable as a cosy fire as well as a barbecue. The brazier must be placed and used securely so it doesn't represent a fire hazard. If charcoals are used as heating-source, the fireplace is regarded as an ordinary barbecue. Be aware of any local restrictions on the use of open fire.

Use of the fireplace must be performed with consideration. Before you kindle the fire, the following must be adhered to. If the surface is inflammable, such as withered grass, it is possible the radiant heat which radiates from the bottom part of the fireplace ignites the grass. It may be necessary to insulate the bottom using a 4-5cm even layer of non-flammable insulation-material or an even layer of 4-5cm sand.

The fireplace is made of sturdy materials and is able to stand the intense heat from a blazing fire. If you want a cosy fire, use regular cleaved firewood. Do not stoke the fire to the extent so the fireplace gets overloaded. If the fireplace is used as barbecue, you may use charcoal as your source of heat. If your source of heat is firewood, you will obtain the optimal combustion and control of the fire by stoking dry firewood cleaved into smaller pieces, no larger than the cardboard-tube inside a kitchen towel. Embers are the standard heat-source when barbecuing, as they provide a moderate heat, while a blazing fire is necessary, when you work with baking-sheet or frying-pan, for example when baking pancakes, as it provides an intense heat.

The grid is adjusted in height using the 4 finger-screws provided.

Transporting the brazier around in the garden/in the playground is done easily using a sack truck.

Alternatively it may be carried by 2 persons using the circular handle. If you are by yourself, you may place the fireplace in a vertical position and roll it along using the handle as base.

Maintenance: Ashes are removed from the fireplace as needed. It's a good idea to oil the iron-parts using a small amount of linseed oil. This is repeated as needed.

If you have further questions, please contact your distributor.

December 2003

www.ACTOY.DK