

Product technical sheet

ROBINIA RB1313







5+

5 kids

36,2 m²





- \bullet Construction made of Robinia very durable acacia wood with a diameter of \sim 18 cm without sharp edges, resistant to weather conditions,
- Platforms made of Robinia very durable acacia wood, resistant to weather conditions,
- Side panels made of Robinia very durable acacia wood without sharp edges, resistant to weather conditions
- Slides made of stainless steel.
- Steel ropes in polypropylene braid, connected with durable plastic elements, stainless steel or aluminum,
- Calibrated stainless steel chains, preventing fingers entrapment,
- Handles made of steel rope in polypropylene braid,
- Screws covered with plastic caps and/or stainless steel screws,



Physical development



balance community



sliding



climbing










number of activity

760 460 HIC 165 18,9 m² 150 150 405 742 HIC 120 2,5 m HIC 100 (S) 36,2 m²





Product technical sheet

ROBINIA RB1313

Product data

Length	460 cm	
Width	405 cm	
Total height	340 cm	
Age group	5+ years	
Number of users	5 kids	
Safety zone	36,2 m2	
Free fall height	165 cm	
The height of the platforms	150 cm	
slide platform height	150 cm	
In accordance with norm EN	1176-1:2017	
Weight of the heaviest part	eaviest part 97 kg	
Dimensions of the largest part	420x18x18 cm	
Availability of spare parts	YES	
Installation time	6 h	

Data is subject to change without prior notice.

Additional information

- equipment intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jimming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70 cm deep;
- slide should not be installed southwards;
- render is for reference only, the actual appearance of the equipment and its color may vary;

Guarantee



30 year guarantee -Structural strength of steel and stainless steel components



15 year guarantee -Structural failure of steel and stainless steel, for dynamic equipment



10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components



5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Detailed information in the guarantee card

Vinci Group Sp. z o.o. Seminaryjna 9 Street 99-400 Łowicz

VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991





Surfaces according to EN 1176-1:2017

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
bark (A,C) Particle size from 20 to 80	30	≤200	
	to 80	40	≤300
woodchips (A,C) Particle size from 5 to 30	30	≤200	
	to 30	40	≤300
sand or gravel (A,C) Particle size fr 0,25 to 8	Particle size from	30	≤200
	0,25 to 8	40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		165

Amount of safe surface corresponding with free fall height:

ROBINIA RB1313

Product technical sheet

HIC 100	6,1 m ²
HIC 120	2,5 m ²
HIC 150	8,7 m ²
HIC 165	18,9 m²

Data is subject to change without prior notice.

